

Parafuso Cabeça Sextavada Pesada Rosca Parcial - A307 Grau B

Diâmetro Rosca (d)	1/2"	5/8"	3/4"	7/8"	1"	1 1/8"	1 1/4"	1 3/8"	1 1/2"	1 3/4"	2"
Rosca / FPP	UNC 13	UNC 11	UNC 10	UNC 9	UNC 8	UNC 7	UNC 7	UNC 6	UNC 6	UNC 5	UNC 4.1/2
Chave Polegada (S)	7/8"	1-1/16"	1-1/4"	1-7/16"	1-5/8"	1-13/16	2"	2-3/16"	2-3/8"	2-3/4"	3-1/8"
Chave mm (S)	22,22	26,98	31,75	36,51	41,27	46,03	50,80	55,56	60,32	69,85	79,37
Alt. Cabeça mm (h)	8,20	10,23	12,26	14,30	15,92	18,23	20,65	21,00	24,73	28,00	30,00
Comp. Rosca mm (b)	34,00	41,00	47,00	53,00	60,00	66,00	72,00	78,50	85,00	98,00	110,00
Comprimento Pol. (L)											
1 1/4"	5,050										
1 1/2"	5,700	9,500	14,800								
1 3/4"	6,300	10,500	16,200	23,600							
2"	6,900	11,500	17,600	25,500	34,600						
2 1/4"	7,500	12,500	19,000	27,300	36,900	48,700					
2 1/2"	8,150	13,400	20,500	29,300	39,600	51,900	67,900				
2 3/4"	8,800	14,400	21,900	31,300	41,900	54,900	71,900	89,950			
3"	9,400	15,400	23,300	33,200	44,600	58,200	75,900	93,850	117,850		
3 1/4"	10,000	16,400	24,600	35,000	46,900	61,400	79,900	98,950	122,500	171,900	
3 1/2"	10,600	17,400	26,000	36,900	49,100	64,700	83,900	103,500	128,600	178,900	244,800
3 3/4"	11,200	18,300	27,400	39,100	51,900	67,800	87,900	108,900	134,500	185,800	254,900
4"	11,800	19,300	28,800	41,000	53,900	70,850	91,900	113,900	140,600	193,500	262,500
4 1/4"	12,400	20,300	30,300	42,700	56,700	73,900	95,900	117,900	145,500	201,600	271,500
4 1/2"	13,100	21,200	31,700	44,500	59,100	77,400	99,400	122,800	150,600	208,800	281,500
4 3/4"	13,700	22,200	33,200	46,800	61,900	80,400	102,900	127,500	156,900	216,500	291,900
5"	14,300	23,200	34,600	48,500	63,900	83,900	106,900	132,500	162,800	223,500	301,700
5 1/4"	15,000	24,200	36,000	50,400	66,800	86,900	110,900	137,400	167,500	231,500	311,400
5 1/2"	15,600	25,200	37,400	52,600	69,400	90,400	114,900	142,600	173,600	239,900	322,500
5 3/4"	16,200	26,100	38,800	54,500	71,900	93,100	118,900	146,500	179,500	245,800	331,400
6"	16,800	27,100	40,100	56,300	74,600	96,400	122,850	151,850	185,900	254,800	341,900

Aplicações: Utilizado em estruturas metálicas, conexões, flanges, etc.

Material: Aço baixo carbono

Dimensões: Conforme ASTM A 307-B / ANSI B 18.2.1

Unidade de Venda: Kg/CT

