

Parafuso Cabeça Sextavada Rosca Inteira - Grau 5

Diâm. Rosca (d)	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Rosca / FPP	UNC 20	UNC 18	UNC 16	UNC 13	UNC 11	UNC 10	UNC 9	UNC 8
Chave Pol. (s)	7/16"	1/2"	9/16"	3/4"	15/16"	1 1/8"	1 5/16"	1 1/2"
Alt. Cab. mm (h)	4,14	5,33	6,17	8,20	10,23	12,26	14,30	15,92
Comp. Pol. (L)								
1/2"	0,532	0,880	1,315					
5/8"	0,583	0,990	1,410	2,985				
3/4"	0,630	1,070	1,580	3,300				
7/8"	0,682	1,155	1,720	3,552				
1"	0,760	1,280	1,850	3,700	6,760	10,860		
1 1/4"	0,860	1,440	2,160	4,300	7,520	11,990		
1 1/2"	0,980	1,645	2,400	4,740	8,049	13,030	19,165	
1 3/4"	1,090	1,805	2,660	5,200	9,190	14,165	16,755	
2"	1,210	2,000	2,915	5,770	9,617	15,349	22,425	31,150
2 1/4"	1,298	2,180	3,210	6,270	10,512	16,510	23,925	32,900
2 1/2"	1,460	2,350	3,485	6,620	11,312	17,485	25,600	35,200
2 3/4"	1,590	2,590	3,850	7,190	12,112	18,643	27,500	37,400
3"	1,640	2,759	4,054	7,750	12,913	19,715	28,975	39,500
3 1/2"	1,865	3,150	4,560	8,590	14,200	22,265	32,100	43,500
4"	2,090	3,518	5,100	9,780	15,800	24,650	34,900	48,250
4 1/2"				10,610	17,716	26,775	38,200	51,400
5"				11,570	19,317	28,920	42,220	55,800
5 1/2"				12,695	20,918	31,340	45,680	60,500
6"				13,470	22,411	33,780	47,800	64,700

Aplicações: Utilizados em máquinas, equipamentos e outras aplicações.

Material: Aço médio carbono temperado e revenido

Dimensões: Conforme ANSI B 18.2.1

Unidade de Venda: Kg/CT

