

Parafuso Cabeça Sextavada Rosca Inteira Inox 304

Diâm. Rosca Pol. (d)	1/4"	5/16"	3/8"	1/2"	1/2"	5/8"	3/4"	7/8"	1"
Rosca / FPP	UNC 20	UNC 18	UNC 16	UNC 13	WW 12	UNC 11	UNC 10	UNC 9	UNC 8
Chave Polegada (s)	7/16"	1/2"	9/16"	3/4"	3/4"	15/16"	1-1/8"	1-5/16"	1-1/2"
Chave mm (s)	11,11	12,70	14,27	19,05	19,05	23,81	28,57	33,33	38,10
Alt. Cabeça mm (h)	4,14	5,33	6,17	8,20	8,20	10,23	12,26	14,30	15,92
Comprimento Pol. (L)									
1/2"	0,534	0,875	1,297						
5/8"	0,590	0,972	1,439						
3/4"	0,652	1,084	1,571	3,263	3,122				
7/8"	0,700	1,164	1,730	3,552	3,332				
1"	0,756	1,259	1,860	3,801	3,610	6,716	10,850		
1 1/4"	0,882	1,455	2,154	4,256	4,166	7,480	11,876		
1 1/2"	1,005	1,639	2,394	4,755	4,567	8,231	12,952	19,229	
1 3/4"	1,113	1,841	2,657	5,296	5,031	9,007	14,248	19,865	
2"	1,237	2,032	2,959	5,802	5,530	9,807	15,228	22,437	31,110
2 1/4"	1,332	2,217	3,236	6,279	5,987	10,600	16,385	23,967	32,940
2 1/2"	1,449	2,429	3,515	6,759	6,511	11,468	17,861	25,597	35,190
2 3/4"	1,578	2,582	3,781	7,267	6,947	12,172	18,732	27,010	37,800
3"	1,704	2,785	4,059	7,783	7,523	12,958	19,757	28,780	39,633
3 1/2"	1,919	3,137	4,630	8,767	8,408	14,588	22,447	32,340	43,573
4"	2,172	3,527	5,180	10,015	9,420	16,038	24,500	35,330	47,740
4 1/2"	2,355	3,839	5,683	10,672	10,400	17,727	26,840	38,330	51,880
5"	2,589	4,291	6,215	11,840	11,452	19,277	29,310	42,130	56,660
5 1/2"		4,648	6,751	12,624	12,596	20,920	31,820	45,430	60,880
6"		5,034	7,347	13,821	13,408	22,620	34,300	48,333	65,337

Aplicações: Utilizados em máquinas, equipamentos e outras aplicações.

Unidade de Venda: Kg/CT

Material: Aço Inox ANSI 304

Dimensões: Conforme ANSI B 18.2.1

