

Parafuso Cabeça Sextavada Rosca Parcial 8.8 DIN 931

Diâmetro Rosca (d)	M-6	M-8	M-10	M-12	M-16	M-20	M-24	M-27	M-30	M-33	M-36
Passo	MA 1,00	MA 1,25	MA 1,50	MA 1,75	MA 2,00	MA 2,50	MA 3,00	MA 3,00	MA 3,50	MA 3,50	MA 4,00
Chave mm	10,00	13,00	17,00	19,00	24,00	30,00	36,00	41,00	46,00	50,00	55,00
Alt. Cabeça mm (H)	4,15	5,65	7,18	8,18	10,18	13,21	15,21	17,21	19,26	21,26	23,26
Compr. Rosca se L <= 125 mm (b)	18,00	22,00	26,00	30,00	38,00	46,00	54,00	60,00	66,00	72,00	78,00
Compr. Rosca se L > 125 mm (b)	24,00	28,00	32,00	36,00	44,00	52,00	60,00	66,00	72,00	78,00	84,00
Compr. Rosca se L > 200 mm (b)			45,00	49,00	57,00	65,00	73,00	79,00	85,00	91,00	97,00
Comprimento mm (L)											
40	0,984	2,046	3,216								
45	1,119	2,077	3,537	4,187							
50	1,184	2,320	3,838	5,496	10,320						
55	1,311	2,472	4,428	5,944	10,992						
60	1,398	2,661	4,432	6,133	11,992						
65	1,485	2,855	4,757	6,748	12,670	21,470					
70	1,606	3,026	5,008	7,294	13,520	22,300					
75	1,727	3,229	5,322	7,622	15,363	23,351	35,270				
80	1,821	3,421	5,607	8,139	15,084	24,790	37,673	49,191			
90	2,077	4,086	6,216	8,999	16,587	27,220	40,853	53,600	68,602		
100	2,333	4,205	6,816	9,808	18,203	29,829	44,613	58,200	68,800	93,107	
110	2,565	4,515	7,380	10,807	19,707	32,183	48,937	62,640	80,302	98,500	122,301
120	2,795	4,919	8,032	11,528	21,367	34,560	51,433	67,161	85,600	106,300	130,000
130		5,293	9,139	12,477	22,707	36,880	54,190	71,200	90,600	112,106	136,600
140		5,667	10,202	13,392	24,680	39,393	58,220	76,280	95,961	18,600	144,000
150		6,041	10,468	14,273	25,933	41,693	63,600	80,362	101,301	126,000	151,600
160			10,340	15,168	27,343	44,073	63,900	85,850	106,409	132,000	160,000
170			10,934	16,061	29,103	46,523	67,500	88,802	112,809	137,800	167,000
180			11,528	16,954	30,253	49,173	72,320	93,805	118,204	144,400	175,000
190			12,122	17,847	31,770	49,873	74,800	98,401	123,305	150,800	182,600
200			12,716	18,740	33,485	53,848	77,860	102,105	128,708	157,200	190,200
220			13,910	20,526	36,510	58,730	85,020	110,801	139,670	170,000	205,400
250			15,670	23,205	41,040	66,050	95,310	123,850	156,110	190,500	228,850

Aplicações: Utilizados em máquinas, equipamentos e outras aplicações.

Material: Aço médio carbono temperado e revenido.

Dimensões: Conforme DIN 931

Unidade de Venda: Kg/CT

