


Parafuso Sextavado Estrutural - A394

Diâm. Rosca (d)	1/2"	5/8"	3/4"	7/8"	1"
Rosca / FPP	13 UNC	11 UNC	10 UNC	9 UNC	8 UNC
Chave Pol. (S)	3/4"	15/16"	1 1/8"	1 5/16"	1 1/2"
Alt. Cab. mm (h)	7,70	9,60	11,55	13,50	15,01
Comp. Ros. mm (b)	26,00	29,00	31,50	34,00	37,00
Comp. Pol. (L)					
1 1/4"	4,517	7,885			
1 1/2"	4,864	8,346	12,975	20,700	31,800
1 3/4"	5,493	9,406	14,409	22,400	33,900
2"	6,052	10,301	16,142	24,100	36,000
2 1/4"	6,712	11,371	17,120	25,270	38,200
2 1/2"	7,410	12,301	18,676	27,500	40,600
2 3/4"	8,197	13,274	19,976	29,300	43,000
3"	9,100	14,254	21,323	31,200	41,910
3 1/4"	9,700	15,700	23,102	33,100	48,000
3 1/2"	10,350	16,700	24,203	35,100	50,200
3 3/4"	11,000	17,600	25,885	36,900	53,000
4"	11,600	18,600	27,800	38,800	55,200
4 1/4"	12,200	19,600	29,100	40,600	57,500
4 1/2"	12,800	20,500	30,500	42,500	60,200
4 3/4"	13,400	21,400	31,800	44,300	62,500
5"	14,100	22,400	33,200	46,200	63,500
5 1/4"	14,800	23,400	34,600	48,500	64,800
5 1/2"	15,500	24,300	36,000	50,200	67,700
5 3/4"	16,200	25,200	37,400	52,100	70,000
6"	16,900	26,100	38,700	54,000	72,500



Aplicações: utilizado na construção civil, montagens de estruturas metálicas, montagens industriais, torres de transmissão de energia, etc.

Material: Aço baixo carbono.
(obs: acab. galvanizado à fogo)

Unidade de Venda: Kg/CT

Dimensões: Conforme ANSI B 18.2.6