


## Parafuso Cabeça Chata com Sextavado Interno Polegada

Diâmetro Rosca (d)	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"
Rosca / FPP	UNC 24	UNC 20	UNC 18	UNC 16	UNC 13	UNC 11	UNC 10
Chave Pol / mm (S)	1/8"-3,17	5/32"-3,96	3/16"-4,76	7/32"-5,55	5/16"-7,93	3/8"-9,52	1/2"-12,70
Alt. Cab. mm (h)	3,22	4,09	5,02	5,94	6,37	8,22	10,05
Diâm. Cab mm (D)	9,11	12,19	15,24	18,28	22,14	28,24	34,41
Comp. Rosca mm (b)	22,22	25,40	28,44	31,75	38,10	44,45	50,80
Comp. Polegada (L)							
1/4"							
3/8"							
1/2"	0,200	0,390					
5/8"	0,240	0,450	0,760				
3/4"	0,270	0,510	0,850	1,310			
1"	0,340	0,630	1,050	1,590	2,670		
1 1/4"	0,400	0,750	1,240	1,870	3,180	5,397	8,011
1 1/2"	0,510	0,870	1,430	2,150	3,690	5,988	9,204
1 3/4"		1,050	1,620	2,430	4,200	6,579	10,282
2"		1,170	1,940	2,710	4,710	7,331	11,220
2 1/4"				3,170	5,220	8,348	12,584
2 1/2"				3,460	6,000	9,100	13,640
3"				4,150	7,030	10,605	15,975



Unidade de Venda: Kg/CT