

## Parafuso Cabeça Cilíndrica com Sextavado Interno (série 1960)

Diâm. Rosca (d)	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	1/2"	5/8"	3/4"	7/8"	1"	1 1/4"	1 1/2"
Rosca / FPP	UNC 24	UNC 20	UNC 18	UNC 16	UNC 14	UNC 13	WW 12	UNC 11	UNC 10	UNC 9	UNC 8	UNC 7	UNC 6
Chave mm (s)	3,96	4,76	6,35	7,93	9,52	9,52	9,52	12,70	15,87	19,05	19,05	22,22	1"
Alt. Cab. mm (h)	4,82	6,35	7,92	9,52	11,12	12,70	12,70	15,87	19,05	22,22	25,40	31,75	1 1/2"
Diã. Cab. mm (D)	7,92	9,52	11,91	14,27	16,66	19,05	19,05	23,82	28,57	33,32	38,10	47,62	2 1/4"
Com. Ros. mm (b)	22,22	25,40	28,44	31,75	35,05	38,10	38,10	44,45	50,80	57,15	63,50	79,24	3 3/4"
Com. Poleg. (L)													
3/8"		0,470	0,830										
1/2"		0,530	0,930	1,490									
5/8"		0,590	1,030	1,630									
3/4"		0,650	1,130	1,740	2,280	3,860	3,860						
7/8"		0,710	1,230	1,910									
1"		0,770	1,330	2,060	2,670	4,370	4,370	7,230					
1 1/4"		0,890	1,520	2,340	3,230	4,880	4,880	8,100	12,280				
1 1/2"		1,070	1,710	2,620	3,790	5,390	5,390	8,970	13,550	21,480	27,700		
1 3/4"		1,190	2,010	3,020	4,180	5,900	5,900	9,840	14,820		34,050		
2"		1,380	2,210	3,310	4,750	6,410	6,410	10,700	16,070	24,960	36,250		
2 1/4"		1,500	2,500	3,710		7,210	7,210	11,570	17,320	26,680	38,350		
2 1/2"		1,690	2,700	4,000	5,700	7,730	7,730	12,180	18,590	28,400	40,550	71,600	
2 3/4"		1,810	2,980	4,400		8,250	8,250	12,970	19,840	30,140	42,750		
3"		1,990	3,180	4,700	6,650	9,080	9,080	13,780	20,810	31,880	44,850	78,300	125,600
3 1/4"		2,170	3,460	5,100									
3 1/2"			3,690	5,390	7,600	10,100	10,100	15,850	23,170	34,670	50,250	85,000	135,400
4"			4,180	6,090	8,550	11,500	11,500	17,920	26,350	37,920	54,250	91,700	145,100
4 1/2"			4,660	6,790		12,800	12,800	19,520	28,710	42,200	59,950	100,000	154,800
5"								21,590	31,870	45,490	63,950	106,800	164,600
5 1/2"								23,650	34,200	49,730	69,550	115,200	177,100
6"								25,260	37,410	53,020	73,750	122,000	186,900
6 1/2"								27,330	39,760	57,260	79,350	131,000	199,900
7"								29,400	42,940	60,550	83,450	137,700	209,600
8"								33,070	48,480	68,080	93,250	153,400	232,300
10"												184,800	277,700
12"												216,200	323,100

**Aplicações:** Utilizado em manutenção geral, máquinas e equipamentos industriais, ferramentaria e outras aplicações.

**Material:** Aço liga temperado e revenido.

**Dimensões:** Conforme ANSI B 18.3 - série 1960

**Unidade de Venda:** Kg/CT

