

Parafuso Cabeça Sextavada Rosca Inteira Inox 304 DIN 933

Diâm. Rosca (d)	M-6	M-8	M-10	M-12	M-16	M-20	M-24	M-27	M-30	M-33	M-36
Passo	MA-1,00	MA-1,25	MA-1,50	MA-1,75	MA-2,00	MA-2,50	MA-3,00	MA-3,00	MA-3,50	MA-3,50	MA-4,00
Chave (S)	10,00	13,00	17,00	19,00	24,00	30,00	36,00	41,00	46,00	50,00	55,00
Alt. Cab. mm (h)	4,15	5,65	7,18	8,18	10,18	13,21	15,21	17,21	19,26	21,26	23,26
Comprim. (L)											
10	0,416	0,875									
12	0,450	0,920	1,760								
16	0,520	1,038	1,966	2,829							
20	0,595	1,194	2,154	3,107	6,271						
25	0,677	1,333	2,388	3,468	6,903	12,000					
30	0,763	1,494	2,656	3,818	7,543	13,420					
35	0,854	1,656	2,880	4,201	8,264	14,324					
40	0,930	1,803	3,142	4,671	9,019	15,416	24,107				
45	1,015	1,961	3,365	4,858	9,615	16,584	25,750				
50	1,109	2,098	3,617	5,282	10,163	17,500	27,240	37,600			
55	1,194	2,270	3,884	5,667	10,916	18,833	28,670	38,363			
60	1,251	2,422	4,074	6,007	11,668	19,587	30,150	41,100	53,700	64,840	
65	1,354	2,580	4,361	6,355	12,248	20,767	31,509	43,046	55,680	68,350	
70	1,451	2,737	4,642	6,754	12,928	21,460	33,450	45,200	58,000	71,200	92,020
75	1,528	2,897	4,864	7,071	13,500	22,617	34,753	47,551	60,421	74,436	93,952
80	1,616	3,077	5,088	7,451	14,196	23,697	36,133	48,700	63,200	76,900	98,205
90	1,784	3,373	5,582	8,052	15,637	25,790	39,340	52,600	67,500	82,300	105,045
100	1,960	3,647	6,075	8,840	16,945	27,880	42,160	56,613	72,700	87,400	111,050
110		3,943	6,256	9,550	18,257	29,953	45,053	60,400	77,570	94,300	118,800
120		4,253	7,023	10,360	19,547	31,960	47,433	64,000	82,200	100,600	125,140
130		4,534	7,539	11,068	20,617	33,950	49,620				
140		4,861	7,759	11,796	21,993	36,020	53,520				
150		5,248	8,608	12,384	23,580	38,523	56,380				
160											
170											
190											
200											

Aplicações: Utilizados em máquinas, equipamentos e outras aplicações.

Unidade de Venda: Kg/CT

Material: Aço Inox ANSI 304

Dimensões: Conforme DIN 933

